

Certificate

Certified Passive House Component

for cool, temperate climates; valid until 31.12.2015

Category: Window Frame

Manufacturer: Alumil S.A.

61100 Kilkis, GREECE

Product name: **S91**

This certificate was awarded based on the following criteria:

Given a Ug value of 0.70 W/(m²K) and a window size of 1.23 m by 1.48 m,

 $U_W = 0.79 \text{ W/(m}^2\text{K}) \le 0.80 \text{ W/(m}^2\text{K})$

Taking into account the installation based thermal bridges and provided that the installation is, with regard to the thermal bridges, equal or better than shown in the data sheet, the window meets the following criterion.

 $U_{W,installed} \leq 0.85 \text{ W/(m}^2\text{K)}$


Thermal data

	U _f -value [W/(m²K)]	Width [mm]	Ψ _g [W/(mK)]	f _{Rsi=0.25}
Spacer			SWISSP.	Ultimate*
Bottom	0.78	178	0.025	0.76
Side/top	0.78	178	0.025	0.76

*Spacers of lower thermal quality, especially those made of aluminium, lead to significantly higher thermal losses and lower temperature factors.

For further information, please see the data sheet

Passive House Institute Dr. Wolfgang Feist 64283 Darmstadt GERMANY



Passive House Efficiency Class

phA advanced component

phB basic component

phC certifiable component

not suitable for Passive Houses

